

**AITCHISON**

# EARTHQUAKER



**SOIL AERATORS AND SUB-SOILERS**



# EARTHQUAKER

- Available in 2 frame sizes - 1.83 m (6 ft) and 2.44m (8ft) wide, with 2 bar high tensile frames.
- Cast clamp components are heat treated SG iron and will not fracture.
- Tines and clamps can be positioned where required along both beams.
- Straight or Parabolic tine legs available.
- Straight legs are 500mm long and fabricated from 16mm heavy duty Bisalloy steel.
- Parabolic tines up to 30% easier to pull.
- Tine legs are angled at a 5 degree lead and do not bring rubbish to the surface.
- Knock on/off Ni-hard toe and wings to ensure excellent sub-soil crackage.
- Flared point design reduces drag and are easier to pull.
- 20mm shearbolts on tine legs.
- Chisel Plough point adaptor available to convert Subtill Aerator to a Chisel Plough.
- Large 350mm (14") disc coulters.
- Optional roller kits available for added depth control.

## 1.83M (6FT) Double Bar Frame

TINE DESCRIPTION	MODEL CODE	NUMBER OF TINES
Straight Leg and Disc Coulter	ST6403	3
	ST6404	4
	ST6405	5
Parabolic Leg and Disc Coulter	ST6503	3
	ST6504	4
	ST6505	5

## 2.44m (8ft) Double Bar Frame

TINE DESCRIPTION	MODEL CODE	NUMBER OF TINES
Straight Leg and Disc Coulter	ST8405	5
	ST8407	7
Parabolic Leg and Disc Coulter	ST8505	5
	ST8507	7



enquire now from your authorised dealer



Video—[www.reeseagri.com](http://www.reeseagri.com)



### New Zealand

REESE ENGINEERING LTD.  
PALMERSTON NORTH, NEW ZEALAND  
Tel: (06) 357 9323  
Fax: (06) 354 3155

### Australia

REESE ENGINEERING LTD.  
GEELONG, VICTORIA, AUSTRALIA  
FREEPHONE: 1-800-140-196  
FREEFAX: 1-800-140-195

### USA

REESE AGRI-USA  
BRAYMER, MISSOURI, USA  
TOLLFREE: 800-432-4020  
Fax: (660) 645 2214  
Email: [reese@reese-usa.com](mailto:reese@reese-usa.com)